



## Bag and Cartridge Vessels



## Sizing, Selection, and Shipping Chart for Eden Vessels

Part Number	Recommended Flow Rate (Max)	Number of Cartridges	Height	Outside Diameter	Standard Inlet	Standard Outlet	Vent Gauge	Leg Length	Weight in Crate (Approx)
<b>Bag Filter Vessels – Rated to 150PSI; designed to meet or exceed ASME Section X Standards</b>									
1EFB1-2C150	60 GPM	Type 1 bag	35"	11"	2" NPT	2" NPT	1/4"	6"	105 lbs.
2EFB2-2C150	120 GPM	Type 2 bag	45"	11"	2" NPT	2" NPT	1/4"	6"	140 lbs.
2EFB2-3C150	160 GPM	Type 2 bag	45"	11"	3" NPT	3" NPT	1/4"	10"	145 lbs.
<b>Cartridge Filter Vessels - Rated up to 150PSI; designed to meet or exceed ASME Section X Standards</b>									
6EFC1-2C150	30 GPM	6 X 10"	25"	11"	2" NPT	2" NPT	1/4"	6"	85 lbs.
12EFC2-2C150	60 GPM	6 X 20"	35"	11"	2" NPT	2" NPT	1/4"	6"	110 lbs.
18EFC3-2C150	90 GPM	6 X 30"	45"	11"	2" NPT	2" NPT	1/4"	6"	115 lbs.
24EFC4-2C150	120 GPM	6 X 40"	55"	11"	2" NPT	2" NPT	1/4"	6"	125 lbs.
20EFC5-3C150	100 GPM	10 X 20"	38"	14"	3" NPT	3" NPT	1/4"	10"	145 lbs.
30EFC5-3C150	150 GPM	10 X 30"	48"	14"	3" NPT	3" NPT	1/4"	10"	160 lbs.
40EFC5-4C150	200 GPM	10 X 40"	58"	14"	3" NPT	3" NPT	1/4"	10"	210 lbs.
50EFC5-5C150	250 GPM	10 X 50"	68"	14"	3" NPT	3" NPT	1/4"	10"	240 lbs.
44EFC2-4C150	220 GPM	22 X 20"	55"	21"	4" slip	4" slip	1/4"	10"	380 lbs.
66EFC3-4C150	330 GPM	22 X 30"	65"	21"	4" slip	4" slip	1/4"	10"	420 lbs.
88EFC4-4C150	440 GPM	22 X 40"	75"	21"	4" slip	4" slip	1/4"	10"	490 lbs.
110EFC5-4C150	550 GPM	22 X 50"	85"	21"	4" slip	4" slip	1/4"	10"	520 lbs.
108EFC2-6FC100	540 GPM	54 X 20"	70"	30"	6" flange	6" flange	3/4"	22"	925 lbs.
162EFC3-6FC100	810 GPM	54 X 30"	80"	30"	6" flange	6" flange	3/4"	22"	1020 lbs.
216EFC4-6FC100	1080 GPM	54 X 40"	90"	30"	6" flange	6" flange	3/4"	22"	1085 lbs.
240EFCV3-8FC100	1200 GPM	80 X 30"	84"	36"	8" flange	8" flange	3/4"	26"	1200 lbs.
320EFCV4-8FC100	1600 GPM	80 X 40"	94"	36"	8" flange	8" flange	3/4"	26"	1550 lbs.
400EFCV5-8FC100	2000 GPM	80 X 50"	104"	36"	8" flange	8" flange	3/4"	26"	1650 lbs.

**\*\*We can customize any vessel for most applications; vessels also available in a horizontal configuration\*\***



## Bag and Cartridge Vessels

Part Number	Recommended Flow Rate (Max)	Bag Type	Height	Width	Length	Standard Inlet	Standard Outlet	Vent Gauge	System Type
<i>Duo Bag Filter Systems - Skid mounted systems; rated to 150PSI</i>									
1EFB1-2FC150M	80 GPM	Type 1	45"	27"	25"	2" flange	2" flange	¼"	Manual
2EFB2-2FC150M	120 GPM	Type 2	55"	27"	25"	2" flange	2" flange	¼"	Manual
2EFB2-3FC150M	160 GPM	Type 2	55"	27"	25"	3" flange	3" flange	¼"	Manual
1EFB1-2FC150A	80 GPM	Type 1	45"	27"	25"	2" flange	2" flange	¼"	Automatic
2EFB2-2FC150A	120 GPM	Type 2	55"	27"	25"	2" flange	2" flange	¼"	Automatic
2EFB2-3FC150A	160 GPM	Type 2	55"	27"	25"	3" flange	3" flange	¼"	Automatic
<i>** Duo filter systems are available with cartridge filter housings; custom configurations also available</i>									

## Vessel Nomenclature Matrix

**88 EFCT 4 - 4F C 150**

